

## NEW Aquarea High Performance Hydraulic Split All in One L Generation Single phase. Heating and Cooling - R290

### Natural refrigerant R290 with GWP 3.

**Energy efficiency:** A+++ in heating at 35 °C and A+ in DHW / DHW up to 65 °C without heater / Stainless steel DHW tank with U-Vacua™ insulation panel / DHW COP up to 3,60.

**Flexibility:** Hydraulic connection between indoor and outdoor / Built-in magnetic water filter.

**Comfort:** Operation without backup heating at -25 °C / 75 °C water outlet temperature maximum at -10 °C outside temperature / 55 °C hot water even at -25 °C outside temperature.

**Control:** Optimised user interface and improved features (2 zone control, bivalent control).

**Connectivity:** Wi-Fi adapter included.



		Single phase (power to indoor)					
Kit 3 kW electric heater		KIT-ADC05L3E5	KIT-ADC07L3E5	KIT-ADC09L3E5			
Kit 6 kW electric heater		KIT-ADC05L6E5	KIT-ADC07L6E5	KIT-ADC09L6E5			
Heating capacity / COP (A +7 °C, W 35 °C)	kW / COP	5,00/5,05	7,00/4,93	9,00/4,55			
Heating capacity / COP (A +7 °C, W 55 °C)	kW / COP	5,00/3,07	7,00/2,98	8,90/3,03			
Heating capacity / COP (A +2 °C, W 35 °C)	kW / COP	5,00/3,52	6,85/3,43	7,00/3,41			
Heating capacity / COP (A +2 °C, W 55 °C)	kW / COP	5,00/2,34	6,25/2,34	7,00/2,41			
Heating capacity / COP (A -7 °C, W 35 °C)	kW / COP	5,00/3,01	5,80/3,01	7,00/2,80			
Heating capacity / COP (A -7 °C, W 55 °C)	kW / COP	5,00/2,12	5,80/2,12	7,00/2,13			
Cooling capacity / EER (A 35 °C, W 7 °C)	kW / EER	5,00/3,23	7,00/3,03	8,20/2,82			
Cooling capacity / EER (A 35 °C, W 18 °C)	kW / EER	5,00/5,00	7,00/4,73	9,00/4,19			
Heating average climate (W 35 °C / W 55 °C)	Seasonal energy efficiency	SCOP (η <sub>s</sub> %)	5,06/3,63(200/142)	4,96/3,62(195/142)	4,84/3,67(190/144)		
	Energy class <sup>1)</sup>		A+++ / A++	A+++ / A++	A+++ / A++		
Heating warm climate (W 35 °C / W 55 °C)	Seasonal energy efficiency	SCOP (η <sub>s</sub> %)	6,00/4,27(237/168)	6,31/4,52(249/178)	6,44/4,50(255/177)		
	Energy class <sup>1)</sup>		A+++ / A+++	A+++ / A+++	A+++ / A+++		
Heating cold climate (W 35 °C / W 55 °C)	Seasonal energy efficiency	SCOP (η <sub>s</sub> %)	4,25/3,28(167/128)	4,25/3,29(167/129)	4,31/3,33(170/130)		
	Energy class <sup>1)</sup>		A++ / A++	A++ / A++	A++ / A++		
<b>Indoor unit 3 kW electric heater</b>		<b>WH-ADC0509L3E5</b>	<b>WH-ADC0509L3E5</b>	<b>WH-ADC0509L3E5</b>			
<b>Indoor unit 6 kW electric heater</b>		<b>WH-ADC0509L6E5</b>	<b>WH-ADC0509L6E5</b>	<b>WH-ADC0509L6E5</b>			
Sound pressure	Heat / Cool	dB(A)	28/28	28/28	28/28		
Dimension	H x W x D	mm	1642 x 599 x 602	1642 x 599 x 602	1642 x 599 x 602		
Net weight 3 kW / 6 kW		kg	93/94	93/94	93/94		
Water pipe connector	Room	Inch	1/4	1/4	1/4		
	Shower	Inch	3/4	3/4	3/4		
A class pump	Number of speeds		Variable Speed	Variable Speed	Variable Speed		
	Input power (Min/Max)	W	30/145	30/145	30/145		
Heating water flow (ΔT=5 K, 35 °C)		L/min	14,3	20,1	25,8		
Water volume		L	185	185	185		
Maximum DHW temperature		°C	65	65	65		
Material inside tank			Stainless steel	Stainless steel	Stainless steel		
Tapping profile according EN16147			L	L	L		
DHW tank ERP efficiency average / warm / cold <sup>2)</sup>		A+ to F	A+ / A+ / A	A+ / A+ / A	A+ / A+ / A		
DHW tank ERP average climate η / COP <sub>DHW</sub>	η <sub>wh</sub> % / COP <sub>DHW</sub>		146/3,60	146/3,60	146/3,60		
DHW tank ERP warm climate η / COP <sub>DHW</sub>	η <sub>wh</sub> % / COP <sub>DHW</sub>		160/4,00	160/4,00	160/4,00		
DHW tank ERP cold climate η / COP <sub>DHW</sub>	η <sub>wh</sub> % / COP <sub>DHW</sub>		112/2,80	112/2,80	112/2,80		
<b>Outdoor unit</b>		<b>WH-WDG05LE5</b>	<b>WH-WDG07LE5</b>	<b>WH-WDG09LE5</b>			
Sound power <sup>3)</sup>	Heat	dB(A)	52	53	54		
Dimension / Net weight	H x W x D	mm / kg	996 x 980 x 430/98	996 x 980 x 430/98	996 x 980 x 430/97		
Refrigerant (R290) / CO <sub>2</sub> Eq.		kg / T	0,96/0,003	0,96/0,003	1,00/0,003		
Water pipe connector (indoor / outdoor units)		Inch	1/1	1/1	1/1		
Pipe length range standard / maximum		m	5/30	5/30	5/30		
Elevation difference (in / out)		m	10	10	10		
Operating range - outdoor ambient	Heat	°C	-25 ~ +35	-25 ~ +35	-25 ~ +35		
	Cool	°C	+10 ~ +43	+10 ~ +43	+10 ~ +43		
Water outlet	Heat / Cool	°C	20 ~ 75/5 ~ 20	20 ~ 75/5 ~ 20	20 ~ 75/5 ~ 20		
<b>Electrical information</b>		<b>3 kW heater</b>	<b>6 kW heater</b>	<b>3 kW heater</b>	<b>6 kW heater</b>	<b>3 kW heater</b>	<b>6 kW heater</b>
Electric backup heater	kW	3,00	6,00	3,00	6,00	3,00	6,00
Recommended RCD, supply 1 / 2	A	25/16	25/30	25/16	25/30	25/16	25/30
Recommended minimum cable size, supply 1 / 2 <sup>4)</sup>	mm <sup>2</sup>	3x2,5/3x1,5	3x2,5/3x4,0	3x2,5/3x1,5	3x2,5/3x4,0	3x2,5/3x1,5	3x2,5/3x4,0

1) Scale from A+++ to D. 2) Scale from A+ to F. 3) The sound power level is measured with accordance to EN12102 under conditions of the EN14825 (part load). 4) Check local regulations. \* EER and COP calculation is based in accordance to EN14511. \*\* This product is designed to comply with the European Water Quality Directive 98/83/EC amended by 2015/1787/EU. The lifespan of the product is not guaranteed in the case of the use of groundwater, such as spring water or well water, the use of tap water when salt or other impurities are contained, nor in areas of acidic water quality. Maintenance and warranty costs related to these cases are the customer's responsibility.

Accessories	
<b>CZ-RTW1</b>	Additional remote controller for K and L Generations
<b>CZ-NS5P</b>	Additional functions PCB
<b>PAW-A2W-RTWIRED</b>	Room thermostat

Accessories	
<b>PAW-A2W-RTWIREDLESS</b>	Wireless LCD room thermostat
<b>PAW-A2W-AFVFLV</b>	1 anti-freeze valve. It is required to order 2 valves per system



INTERNET CONTROL: Wi-Fi adapter included.